

# Vacuum Separator VS-06 CLIMABOX



## OPERATING INSTRUCTIONS 2018

Copyright: **Ing. ALTMANN 2018**

Fa. Ing. Altmann, ARS–Altmann Group, **Machova 142, 344 01 Domazlice, Czech Republic, European Union**

Tel: +20-379 738 778, Fax: +420-379 738 775, Cell phone: +420-602 362 157 email: [altmann@iol.cz](mailto:altmann@iol.cz),  
[www.ars-altmann.com](http://www.ars-altmann.com)

<b>CHAPTER 1 TECHNICAL DATA</b>	<b>3</b>
<b>CHAPTER 2 . INSTALLATION</b>	<b>4</b>
<b>CHAPTER 3 . FUNCTION</b>	<b>10</b>
3.1 Computer control	10
3.2 Startup - Procedure	15
3.3 Separation of moisture and gases	18
3.4 Water removal - Procedure	18
3.5 Oil sampling procedure	18
3.6 Shutdown - procedure	18
3.6.1 Main switch	19
3.6.2 Short-term shutdown	19
3.6.3 Long-term shut down	19
3.8 On-line volume measuring of separated water	21
3.9 Stripping procedure : Effective removal of fault gases from the oil	22
<b>CHAPTER 4 . PROTECTIONS</b>	<b>23</b>
4.1 Oil loss	24
4.2 Overpressure	24
4.3 Overfill of external water trap, and discharge of external water trap	25
<b>CHAPTER 5 . ALARMS</b>	<b>27</b>
5.1 STARTUP - ALARM	27
5.2 BATCH UNIT - ALARM	27
<b>CHAPTER 6 . MAINTENANCE</b>	<b>28</b>
6.1 Cleaning of internal surfaces of glas chambers	28
6.2 Input filters – Check & Replacement	28
6.3 Replacement of filter inserts of ultrafilter	29
<b>CHAPTER 7 . ELECTRICAL CIRCUITS</b>	<b>31</b>
Power Circuit diagram is shown on Fig. 8	31
<b>CHAPTER 8 - REMOTE CONTROL</b>	<b>35</b>
<b>CHAPTER 9 THE ADVANCED EVALUATION OF THE EFFECTIVITY OF TRANSFORMER TREATMENT</b>	<b>48</b>

## Chapter 1 Technical data

Power supply voltage	400 V (or on request)
Power supply frequency	50 Hz (or on request)
Power consumption:	
without oil heater	850 W
With oil heater PO-01	5200 W maximum
Air-condition unit	300W
Oil throughput	10 m <sup>3</sup> per day maximum
Outlet water content	10 ppm nominal , 4 ppm minimum
Outlet gas content	1% nominal, 0.3 % minimum
Outlet filtering grade	1 µm
Weight – CLIMABOX version (separator, heater ultrafilter, external water trap, etc.)	
Dry weight ( without oil)	520 kg
Operating weight (oil filled)	580 kg
Hydraulical connection	2 x flexible 1/2" hose
Communication:	faxmodem GSM modem LAN SMS

Operational condition:

Max. surroundings temperature: 60°C  
Max. humidity: 100 %

Min. temperature of dehydrated transformer 40°C

For successful dehydration of transformer and successful oil drying it is necessary to ensure:

**hold the temperature of transformer over 40°C**

## Chapter 2 . Installation

The separator VS-06 A CLIMABOX is attached to the transformer as shown in Fig.1.

Installation procedure:

- attach the oil-inlet set (coupling, insulation insert and servo valve YV4 See Fig.1) to the lower access of the transformer (i.e. bottom filter press cock), then connect to the open end of the servovalve YV4 the in-let hose H1, then connect the opposite end of the hose H1 to the hydraulic connector HC1 (see Fig.2 – right side of the CLIMABOX -cock K-IN), open the cock K-IN
- attach the oil-outlet set (coupling, insulation insert and servo valve YV3 See Fig.1) to the upper access of the transformer (i.e. upper filter press cock), then connect to the open end of the servovalve YV3 the out-let hose H2, then connect the opposite end of the hose H2 to the hydraulic connector HC2 (K-OUT), open cock K-OUT
- remove the face and rear cover of the CLIMABOX
- check if all cocks on right and left side of separator and at the rear side are full open
- check if all 3 filter insterts of the ultrafilter are installed
- connect cable of servo valve YV4 to the input servo-connector
- connect cable of servo valve YV3 to the output servo- connector
- check the correct level of the supply voltage (required 400 V +/- 15V) Five wire connection cable and connector (3x400V, PE,N) is neccesary (N-light blue 0-phase, PE-green-yellow security)
- set the supply circuit breaker (in the power-supply box ) for a minimum load of 16A, then connect the separator to the power-supply box.
- check DC voltage of the data line (required 42-45V), then connect the data transmission cable to the telephone connector

Right side of VS-06 which is used for a hydraulic connection to the transformer, the power supply and the communication, is shown on Fig.2.

Left side of VS-06 is equipped either with air-condition unit (for air temperatures over 40C) or in the left niche is installed the stainless-steel sieve – for air temperatures under 40C.

Flow diagram of VS-06 is shown on Fig. 3.

Detailed internal layout of VS-06 – the face part - inclusive external water trap is shown in Fig. 4.

Rear part of VS-06 is shown in Fig. 5 .

**First start-up of the VS-06 has to be carried out by the manufacturer himself or through from him authorized service technicians.**

### ATTENTION !

Check the oil-level in the conservator tank always before first start up of the VS-06.

- oil level should exceed the minimum mark by 1/3 of the scale in the conservator
- survey this level continuously during the start-up procedure and during the operational condition – the oil level in the conservator tank shall never fall below the minimum level indicator
- if the oil level would fall below the minimum mark of the conservator tank, refill oil immediately or/and use a auxiliary conservator






Fig.1 Installation of VS-06




**Fig. 2** Right side of VS-06 CLIMABOX without cover



1	hermetized pump	19	oil leakage sensor..... BQ3
2	main vacuum chamber	20	flusching valve
3	wet gas accumulation chamber	21	external water trap
4	wet gas separator	22	water removal cock
5	oil accumulator	24	air bleed valve
6	collecting chamber	25	stripping valve YV5
7	inlet ejector		
8	process ejector	P1	pump mano-vacuum gauge
9	gas flow monitoring chamber	BP1	pump pressure sensor
10	batch unit	P2	main chamber gauge
11	cooling chamber	BP2	main chamber pressure sensor
12	cooling compressor..... M3	P3	collecting chamber gauge
13	fan..... M2	BP3	collecting chamber pressure sensor
14	defrosting valve.....YV1	BP4	throughflow pressure sensor
15	fan thermostat .....ST1		
16	exhaust valve	BT1	freezing chamber temperature sensor
17	throttle valve	BQ1	batch unit water level sensor
18	oil trap tube	BQ2	ext. water trap water level sensor


**Fig. 3 The flow diagram of the internal part of the VS-06 CLIMABOX**



1	Hermetized pump	22	Oil leakage sensor
2	main vacuum chamber	23	Proces Control Unit AMIT 4001 A
3	wet gas accumulator	24	Modem US Robotics (or GSM Modem)
4	wet gas separator	25	Main switch box
5	oil accumulator	26	Main switch ..... QM1
6	collecting chamber	27	Autotransformer
7,8	Inlet, process ejector	28	Fan thermostat 2 (external cooling)
9	gas flow monitoring chamber		
10	batch unit		
11	cooling unit		
12	fan thermostat .....ST1		
13	exhaust valve		
14	throttle valve	P1	pump gauge
15	Water level sensor ext. water trap	BP1	pump pressure sensor
16	Return valve (vacuum building)	P2	main chamber gauge
17	External water trap	BP2	main chamber pressure sensor
18	water removal cock	P3	collecting chamber gauge
19	Deslugging cock	BP3	collecting chamber pressure sensor
20	Air bleed valve	BP4	throughflow pressure sensor
21	Oil sump		

**Fig.4 Internal layout of main components in separator VS-06 (without cover)**





1	Ultrafilter	BT2	Heater output temperature sensor
2	Inlet rough filter	BT3	Inlet temperature sensor
3	Inlet fine filter	Bps1	Bypass of fine inlet filter
4	Oil heater	Bps 2	Bypass of outlet filter
KA	auxiliary cock (used e.g. by the exchange of the fine filter (4) or by the cleaning of filter (2))		

**Fig.5 Layout of main components in rear part of separator (without cover)**

## Chapter 3 . Function

### 3.1 Computer control


The Altmann System VS-06 (Vacuum Separator) is designated for on-power dehydration of oil-immersed cellulose insulation systems of power transformers.

The separator is controlled by the „**Process Control Device**“ AMIT ART 4000 F.

Through remote data collection and transmission, **PCD** manages on-line the dehydration process in the separator and in the whole transformer.

**PCD** enables the remote-monitoring of all important parameters of the dehydration process inside of the transformer, and of separator's operation itself.

**PCD** allows to change by remote-control important operative parameters of the separator in order to guarantee optimum efficiency.



**Fig. 6 Structure of control & communication of VS-06**

For more details about VS-06 A Remote Control See Chapter 8.

The separator is working practically without any local operator intervention or any necessary operator supervision. The **PCD** is increasing the self-governing autonomy of the separator.

The operator's intervention is limited to:

- ⇒ connecting & disconnecting of the separator to the transformer  
(See **2. Installation**)
- ⇒ startup of the separator by main-switch **QM1**  
(See **Startup – Procedure**)
- ⇒ shutdown of the separator (by main-switch **QM1** or pushing **F2** key on **AMIT** terminal)  
(See **Shutdown – Procedure**)

Any other in-situ usual activities of the operator are:

- ⇒ changing the input and output filter inserts - pushing **F4** key on **AMIT Terminal**  
(See **Filter Changing - Procedure**)
- ⇒ removing water from the external water collector - pushing **F3** key on **AMIT** terminal  
(See **Water removal – Procedure**)

All this activities are computer controlled and supported. Computer recommends operator desired activity on terminal AMIT and checks the results.



Fig. 7 AMIT Terminal & Supply Unit

Protection and any other function of separator are solved in the same way.

Periodical monitoring, change of parameters and all other functions can be realized by remote control.

Table 1 shows list basic programs of VS-06.

These programs are initialized by pushing F1...F4 keys on **AMIT** terminal, or using the keyboard (for parameter changing).

Tree structure is used:

- First step: Select common program by pushing of F1...F4 key
- APT display then shows another menu (second level)

Example:


After pushing the F1 key in the first step, another choice of menus appears: pushing again F1 key for **Parameter change (Parameter Table)** , or F2 for **Manual Defrost** , or F3 for **Manual Control**

- Second step: Pushing of selected key will start the chosen program.

**Table 1 Key control**

KEY	Activity
<b>F1</b>	F1 – Parameter change , F2 – Manual Defrost , F3 – Manual Control
<b>F2</b>	Computer controlled shutdown
<b>F3</b>	Computer controlled Water Removal
<b>F4</b>	Computer controlled filter Check & Replacement.
<b>F5</b>	Computer controlled Oil Sampling

The visual control of input / output relation of the PCD AMIT can be followed by means of LEDs situated under the AMIT Terminal.



LED lighting = ON

Inputs		Outputs	
<b>BQ1</b>	Batch unit water sensor	<b>KM2</b>	Gear pump – direct run
<b>BQ2</b>	Water trap water sensor	<b>KA1</b>	Cooling
<b>BQ3</b>	Oil leakage sensor	<b>KA2</b>	Defrost
<b>FV1</b>	Phase relays	<b>KA3</b>	Flushing
<b>KM1</b>	Oil heating	<b>KA4</b>	Oil input servovalve
<b>KM3</b>	Gear pump – reverse run	<b>KA5</b>	Oil output servovalve
<b>FU5</b>	Fuse 9VAC - modem supply LED lighting = OFF (burned)	<b>FU4</b>	Fuse 24 DVC – control circuits LED lighting = OFF

## Parameter Table

The functions of Vacuum Separator are controlled by basic pre-set parameters and parameters can be changed any time by:

- ⇒ double push of the key F1
- ⇒ rolling display down/ up till requested parameter is shown
- ⇒ pushing Enter to overwrite the given parameter
- ⇒ pushing Enter to confirm new parameter
- ⇒ back to main display via simultaneous pushing of ALT-ENTER

Parameter Table

Value	Description	
P1min	Abs. pressure of inlet section (deaeration)	40 kPa
P2min	Abs. pressure of outlet section (deaeration)	40 kPa
DP1	Pressure difference - cavitation control of gear pump	15 kPa
P2auto	Pressure level of forced removal of gases (reverse run of gear pump)	120 kPa
P2max	Maximal allowed pressure in vacuum vessels	250 kPa
DP2	Pressure difference for forced removal of gases	4 kPa
P2vc	Transition to internal cycle	15 kPa
P2atm	Atmospheric pressure (seal-level), for higher elevation has correspondingly to be changed	105 kPa
DTVC	Time delay of internal cycle	30 sec
Tmax	Max. allowed time-period of freezing cycle	20 min
T1min	Freezing temperature of cooling unit	- 15 C
DT1	Temp. hysteresis of cooling control loop	1 C
T1max	Max. allowed temp. of defrost. process	15 C
Todt	Time-period of defrost. process	5 min.
T1alarm	Max. allowed temp. of defrost. process	20 C
Talarm	Time-delay of T1alarm inicialization	20 min
T2max	Output temp. of oil (preheater )	50 C
DT2	Hysteresis of preheater control loop	5 C
T2alarm	Max. allowed temp. of oil	85 C
Podst	Separator - shut-down removal of oil from both hoses	85 kPa
P2minvac	Minimal allowed pressure ( to avoid water boiling in batch unit)	3 kPa
P3auto	Gas removal from separator	108 kPa
T1MD	Minimal required T1-temp under emergency control	0 C
P1max	Max. allowed pressure in outlet section ( if higher = output probably clogged = ALARM)	450 kPa

P3max	Maximal allowed pressure in non-vacuum vessels	220 kPa
-------	--	---------

#### Parameters of stripping procedure

P2ST	Stripping pressure ( 0 kPa - stripping process OFF)	15 kPa
DTS1	Stripping servovalve ON	10 s
DTS2	Stripping servovalve OFF	20 s

For remote change of main parameters See 8.13 Parametric process control

#### Attention

**All parameters are optimally selected by the producer.  
Don't change them without previous consultation**

### The Setting of internal clock of PCD AMIT

The change of Date and Time of the PCD AMIT according to local conditions can be performed anytime:

- main switch QM1 OFF/ON and immediately ( within ca 3 seconds, maximum) click on key F2
- AMIT displays two rows with date and time e.g.

<b>10.06.16</b>	(date)
<b>06.23.06</b>	(time)

- click on ↑ to change the **date** , enter required date via AMIT keyboard and confirm it by ENTER
- click on ↓ to change the **time** , enter required time via AMIT keyboard and confirm it by ENTER
- for return click on key F1

### 3.2 Startup - Procedure

To start the separator switch the main switch **QM1** on the position I (ON).

The first STARTUP after the first installation of the VS-06 by a new client (*or after the download of a new software*) always begins with the safeguard protocol :

**PASSWORD ?**

**0**

**< ENTER >**

Clicking on ENTER starts the subroutine for entering of the code numbers via PCD Amit keyboard.

**PASSWORD ?**

**\* \* \* \***

**< ENTER >**

Four numbers have to be entered and confirmed by ENTER.

**The safeguard protocol keeps the observance of contract and/or payment conditions.**

#### **ATTENTION :**

**Three attempts are allowed, then the PCD of the VS-06 is completely blocked and its recovery has to be performed either in situ by the producer staff or by remote corol .**

Two kind of PASSWORD are used here :

- **for time-limited operation** ( VS-06 works only for limited time-period defined by the contract conditions - usually for 30 days). Then its VS-06 is automatically switched off and display shows Alarm M. For detailed information concerning the VS-06 restart See Chapter 5 Alarms.
- **for permanent operations** (the client obtains this specific password immediately after the fulfilment of contract conditions. When it is entered the ADT works permanently).

The **APT** display (**23**) shows „date“ and „time“ for checking. You have 5 sec for zero setting of values for T (total time of dehydration), MWC (total amount of separated water until this time in ml) and MW (total water volume in the external water trap in ml).

**VACUUM    SEPARATOR**

**VS-06**

**„date“**

**„time“**

**ZERO SETTING - ENTER**

When the separator is connected to a new transformer for a new dehydration process, the values for T (time of dehydration), MWC (total volume of separated water), MW (actual water volume in the water trap) need to be set to zero.

By pushing ENTER all the registers for T, MWC and MW are set to zero. The display confirms the procedure as follows:

<p><b>VACUUM    SEPARATOR</b></p> <p><b>VS-06</b></p> <p><b>MWC = MW = 0</b></p> <p><b>T = 0</b></p>
--

When we need to conserve the old values for T, MWC and MW, (continuing the dehydration of the transformer in cure, after shut-down of main switch) - do nothing - only wait ca 5 sec and separator will start to work again with the earlier values..

The automatic start-up procedure first evacuates the whole outflow section of separator, display shows:

<p><b>SEPARATOR START UP</b></p> <p><b>VACUUM PROCESSING</b></p> <p><b>IN OUTLET SECTION</b></p> <p><b>P1 = P1    P2= P2 (kPa)</b></p>
--

If pressure **P1** in his section decreases below the preprogrammed absolute pressure [**P1MIN**], then the servovalve **YV3** will open automatically, but the sampling cock is still closed.

**Attention** : If the pressure **P1** will not decrease below [ **P1MIN** ] level, then the Startup procedure will remain in the first step. The vacuumizing of the outflow section is not successful and the outflow servovalve remains in closed position.

The **AMIT Terminal** reports that the desired vacuum is reached and demands the opening of the upper valve (cock) on the transformer main tank

<p><b>OUTLET SECTION</b></p> <p><b>ON VACUUM P1 = P1</b></p> <p><b>OPEN UPPER VALVE(S)</b></p> <p><b>AT MAIN TANK</b></p>
---

And the oil from the main tank will flush this section. The flush of oil from the transformer continues automatically until the whole separator is filled with oil. The **AMIT Terminal** will report:

<p><b>GAS COMPRESSION</b></p> <p><b>P1 = P1    P2 = P2 (kPa)</b></p>
--

If pressure **P2** exceeds preprogrammed absolute pressure [ **P2AUTO** ] and gases are expelled from main chamber and gas accumulator, the **AMIT Terminal** will report Gas Exhaust. This is visible as a stream of gas-bubbles in the glass of the control chamber ( **9** ) and then in the plexi glass extension of the exhaust valve ( **13** )

<p><b>GAS EXHAUST</b></p> <p><b>P1 = P1    P2 = P2 (kPa)</b></p>
--

If the hydrostatic head of the transformer is lower than ca. 1,5 m of the separator, then the filling of the separator is too slow. Automatically the separator pump switches on reverse ON-OFF to force the oil into the separator.



The **AMIT** terminal will report the end of this step and the automatic transition to the next step

**VACUUM PROCESSING  
IN INLET SECTION**

**P1 = P1      P2= P 2 (kPa)**

If pressure **P2** in the separator and in the suction section decreases below the preprogrammed absolute pressure [ **P2MIN** ], then the servovalve **YV4** will open automatically. The **AMIT Terminal** will report:

**INFLOW SECTION  
ON VACUUM  
OPEN BOTTOM VALVE(S)  
AT MAIN TANK**

The whole inlet section is flushed by the oil from the transformer and **AMIT Terminal** will report the end of startup procedure:

**STARTUP FINISHED  
SEPARATOR READY  
FOR TRANSFORMER  
DRYING**

**PCD** – computer controll of the separator will automatically start main hydraulic-vacuum cycle.

### 3.3 Separation of moisture and gases

The VS-06 separator provides moderate vacuum, moderate heat and large interfacial surface, needed to separate gases and vapours from the oil.

All procedures are fully automatized and remote controled, local operator action is not necessary.

### 3.4 Water removal - Procedure

Water removal procedure from **water trap (17)** can be effected any time by pushing **F3** key on **AMIT Terminal**.

The **AMIT Terminal** will report start of water removal procedure accustically and on display:

<p><b>WATER REMOVAL ON PRESSURE EQUALIZATION, WAIT P2 = xxx kPa</b></p>
---

**CAUTION** The water removal cock (**18**) can be opened only if pressure equalization is indicated. Then a water removal procedure is realized, and cock (**18**) must be closed again.

<p><b>OPEN BOTTOM COCK OF WATER TRAP DRAIN OFF WATER PUSH ENTER</b></p>
---

After pusching ENTER separator goes back to normal separation process

### 3.5 Oil sampling procedure

Oil sampling procedure can be started any time by pushing **F5** key on **AMIT Terminal**. The **AMIT Terminal** will report this status as:

<p><b>OIL SAMPLING ON WAIT FOR PRESSURE EQUALIZATION</b></p>
--

**CAUTION** Sampling cock situated under main switch box can be opened only if pressure equalization (PRESSURE OK ) is indicated. When a sampling procedure is made, cock must be of course closed again.

<p><b>PRESSURE OK  SAMPLING FINISHED ? YES - ENTER</b></p>
--

After pusching ENTER separator goes back to normal separation process

### 3.6 Shutdown - procedure

Separator VS-06 can be any time shut down by :

- main switch **QM1**
- key **K2**

### 3.6.1 Main switch

When main switch **QM1** is setted **OFF** in ca 10 sec are closed both servo valves **YV3** and **YV4**. This way is separator quickly a safely disconnect from oil filling of transformer.

When **QM1** is setted **ON** is separator automatically started again

Computer controlled shut- down procedure is inicialized by key **F2**.  
Display offers us two procedures

**FOR SHORT-TERM  
SHUTDOWN - PUSH F7  
FOR LONG-TERM  
SHUTDOWN - PUSH F8**

### 3.6.2 Short-term shutdown

After click on F7 display shows

**SHORT-TERM  
SHUTDOWN ON  
WAIT**

and standard sequence **Water removal** 3.4 is started at first.

Using of **Water removal** procedure as internal procedure of **Short-term shutdown** is necessary especially under very low surrounding temperatures.

When is this procedure finished goes separator back to normal Short-term shutdown procedure.

**: SHORT-TERM  
SHUTDOWN FINISHED  
FOR START TURN OFF/ON  
MAIN SWITCH QM1**

### 3.6.3 Long-term shut down

When water content in the transformer decreases under desired level is dehydration process stopped and separator is transported and connected to another wet transformer .

Separator should be transported without oil and therefore following procedure is used  
After pusshing of F2 is following display shown again

**FOR SHORT-TERM  
SHUTDOWN - PUSH F7  
FOR LONG-TERM  
SHUTDOWN - PUSH F8**

and after pusching **F8** is displayed

**SHUTDOWN FOR**

### TRANSPORTATION ?

**YES - ENTER**

and sequence of another instructions and messages are the same as by *SHORT-TERM procedure*.

When WATER REMOVAL is finished and on the display is indicated

**LONG-TERM SHUTDOWN  
ON  
VACUUM PROCESSING ON  
WAIT**

and servo valve **YV4** closes immediately and stops oil inflow in the separator. The pump is turned on, vacuum is built up and this process continues until separator is emptied.


When proper vacuum is reached, the pump turns off and this state is reported as

**CLOSE BOTTOM COCK  
OF TRANSFORMER  
DISMOUNT VALVE YV4  
PUSH ENTER**

**DISMOUNTING OF SERVOVALVE HAVE TO BE ALWAYS CARRIED OUT WITHOUT  
DISENGAGE OF HOSE only by unscrew of female screw – See following Fig.**

**Only this way remains the hose under vacuum and separator shut-down  
is not disturbed !!**

**THIS PROCEDURE IS THEREFORE VALID FOR DISMOUNTING BOTH SERVO VALVES**



after click on **ENTER** servo valve **YV4** opens and the infowing air is forcing the oil from hose H1 and preheater PO-01 back into separator.

End of this process is reported as

**OIL EXHAUST FINISHED  
CLOSE COCK K-IN  
DISMOUNT HOSE H1  
PUSH ENTER**

and then follows the next procedure for oil-discharging from outflow section.

Begin of this process is indicated as

<b>LONG-TERM SHUTDOWN ON VACUUM PROCESSING ON WAIT</b>
--

and

<b>CLOSE UPPER COCK OF TRANSFORMER DISMOUNT VALVE YV3 PUSH ENTER</b>
--

after pushing of **ENTER** is servo valve **YV3** (dismantled by **unscrew of female screw** from upper cock of transformer ) opened and air from surrounding forces out the oil from hose H2 and ultrafilter back into separator.

End of this process is reported as

<b>OIL EXHAUST FINISHED CLOSE COCK K-OUT DISMOUNT HOSE H2 PUSH ENTER</b>
--

and end of long-term shut-down is reported as

<b>LONG-TERM SHUT-DOWN FINISHED TURN OFF MAIN SWITCH QM1</b>
--

Long-term shutdown of separator is finished when QM1 is switched OFF and power supply cable is dismantled.

**CAUTION ! Separator should be transported in vertical position only !**

### 3.8 On-line volume measuring of separated water

The quantity of separated water is measured by volume, and is stored in the PCD AMIT. From there remote collecting of these data is possible at any time.

At the later stage of the defrosting procedure, water droplets will fall by gravity from the cooling chamber (11) down into the bottom of the glass cylinder of the batch unit (10). When the level of this collected water reaches the water sensor (**BQ1**), a signal as (ca 20 ml of collected water) is passed on to the PCD control unit, and the separator goes to the batch procedure.


The batch procedure is reported on the **AMIT Terminal** as:

<b>WATER BATCHING</b>
<b>ON</b>
<b>WAIT FOR</b>
<b>FLUSHING</b>

The gear pump will run on reverse, and if the pressure **P2** exceeds the preprogrammed pressure level [ **P2AUTO** ] , the flushing valve ( **20** See function diagram on Fig. 3. ) will be opened, and water (and oil) will be pumped from the batch unit into the water trap ( **21** ).

*The batching unit will be flushed twice in order to remove the last water residua, before the whole batching procedure is finalized.*

From the time interval between the last and the present batch procedure, and the volume of transported water, PCD calculates the water removal efficiency **MWT** (ml/24 hod) of separator.




### 3.9 Stripping procedure : Effective removal of fault gases from the oil

The standard separation of gases and moisture under relatively low temperature and vacuum fully satisfies the basic rule of any on-line transformer treatment „ **no-impact on oil properties**“.

Unfortunately this specific process cannot effectively remove heavy fault gases (as CH<sub>2</sub>, C<sub>2</sub>H<sub>4</sub>, C<sub>2</sub>H<sub>2</sub>, C<sub>2</sub>H<sub>6</sub> etc) from a transformer oil inventory especially by treatment of hermetized transformers..

The VS-06 is therefore equipped with stripping valve situated on batch unit See picture below



and, under defined conditions , repeatedly injects a small amount of air into the separator to boost its separation capability.

The stripping process automatically starts as soon as P2-level decreases under predefined P2ST-level and it is finished if the P2-level increases over mentioned level.

The setting in situ via AMIT keyboard: by double click on key F1 and re-writing of P2ST-, DTS1 (servo valve ON) a DTS2 -parameter ( servo valve OFF) in the Parameter Table

REM. The stripping kit isn't standard part of VS-06 and has to be extra ordered .

## Chapter 4 . Protections

The separator VS-06 is designed and build specifically with remote control in order to operate for prolonged time periods without the necessity of any local supervision.

Therefore it is very important that any significant oil-loss will be ruled-out under any circumstances.

#### 4.1 Oil loss


The separator system consists of hermetically sealed hydraulic and condensation circuits and at the rear side is situated the external heater and ultrafilter (See Fig.1 and Fig 4). All these parts are hydraulically connected to the leakage tube in the bottom of the CLIMABOX. Any oil spil in the separator system will be collected in this leakage tube. In the unlikely event of spill, leakage sensor BQ3 (**16** - See Fig.3 and bottom picture) mounted in the lowest part the drip tray of the CLIMABOX will then generate oil loss alarm. Immediatedly the separator is stopped, and the servo valves shut-off.

Thus, in 10 seconds of detecting oil-spill, the transformer will be hydraulically isolated from the separator by closing down of the two servo valves **YV3** and **YV4**,.

The oil-leak alarm is indicated acustically and on the display of the **AMIT Terminal**.

**OIL LEAK  
FIND & REPAIR LEAKAGE  
DRY OUT SENSOR BQ3  
RESET BY QM1 OFF/ON**

After the detecting and sealing of leakage (and drying of container of leakage sensor BQ3 See (F4,16) and the photograph picture showing disassembled sensor), reset the separator by switching main switch **QM1** OFF and ON.



#### 4.2 Overpressure



Hydraulic and vacuum chambers of separator, heater and ultrafilter are protected against overpressure in two levels:

- PCD controls the pressure **P1** and **P2**, and will recognize if these values will exceed the allowed limits [ **P1MAX** ] / [ **P2MAX** ]. If this happens, the separator is automatically shut off, and this state is indicated acoustically and on the display

If pressure P1 on the pump exceeds [ **P1MAX** ], acoustic alarm is generated, and display on **AMIT Terminal** will indicate:

<p><b>OVERPRESSURE P1</b> <b>ALL VALVES &amp; COCKS</b> <b>ON OUTFLOW ARE OPEN ?</b> <b>RESET BY QM1 OFF/ON</b></p>
---

If pressure P2 in the main chamber exceeds [ **P2MAX** ], acoustic alarm is generated, and display on **AMIT Terminal** will indicate:

<p><b>OVERPRESSURE P2</b> <b>CHECK SENSORE BP2</b> <b>BY MEANS GAUGE P2</b> <b>RESET - QM1 OFF/ON</b></p>
---


#### 4.3 Overfill of external water trap, and discharge of external water trap

If water level in the water trap exceeds allowed level, then the water level sensor BQ2 will be activated and separator is shut down. **AMIT Terminal** will display:

**WATER TRAP FULL  
FOR DISCHARGING  
PUSH F3**

Manual water removal from water trap can be made any time under normal operation of the separator, if one simple condition is fulfilled:

The pressure P2 has to be below 100 kPa during the whole removal procedure in order to rule out any unwanted oil-spill.



Manual water removal procedure:

- check the pressure level P2
- remove cap of air bleed valve
- slowly open the air bleed valve
- slowly open the discharging cock and discharge all water from water trap
- close both cocks
- close air bleed valve with cap

#### **ATTENTION !**

**When the separator is shutted-down and the ambient temperatures are deep below 0°C, the water from the external water trap has to be completely removed.**

## Chapter 5 . Alarms

All vital functions of separator are continuously observed, recognized and supervised by PCD. ALARM is generated and indicated if PCD recognizes, that measured parameters will exceed preprogrammed and given criteria or the contract conditions as not fulfilled.

ALARM is indicated on AMIT Terminal and acustically:

ALARM is transmitted to the supervisor by remote PC – See Manual **VS-06 Remote Control**

### 5.1 **STARTUP - ALARM**

	<b>WRONG VOLTAGE OR</b>
	<b>ROTATION DIRECTION</b>
	<b>TURN QM1 OFF , REPAIR</b>
	<b>TURN QM1 ON</b>

### 5.2 **BATCH UNIT - ALARM**

This alarm indicates, that the water sensor **BQ1** of batch unit (**F3,BQ1**) is contiuously under water. PDS evaluates this as choked internal batch filter and the separator is automatically shut off.

**AMIT Terminal** displays:

<b>BATCH UNIT CHOKED</b>
<b>FOR START</b>
<b>TURN QM1 OFF AND ON</b>

The filter is situated in the lower part of batch unit. After Shut-Off of the separator, empty the batch unit by opening the deslugging cock, and open the nut of internal filter. The filter can be easily cleaned with brush, solvent and pressurized air. See picture in Chapter 3.7

### 5.3 **Alarm M**

This alarm indicates the expiration of contract defined payment conditions.

The AMIT terminal displays:

<b>ALARM - M</b>
<b>CALL FOR SERVICE</b>

If contract conditions are fullfild (proper settlement is performed) fy. Altmann will send you the 4-digit Password which enables permanent operation of VS-06.

The restart of VS-06 :

- Main Switch QM1 OFF/ON
- during the first display VS-06, click on Key F4 ( you have ca 3 seconds to do it)
- click on button " Up"
- enter the Pasword :
- click on ENTER
- new restart by QM1 OFF/ON

## Chapter 6 . Maintenance

The VS-06 Separator requires minimum maintenance. Nevertheless, it is recommended that a regular maintenance schedule be established as described in the following sections .

### 6.1 Cleaning of internal surfaces of glas chambers

By dehydration of wet transformer with heavy aged oil is necessary regular cleaning of all glas chambers and cylinders. The cleaning is provided by serviceman of producer or other authorized person.

### 6.2 Input filters – Check & Replacement

Intensity of inflow of oil in separator is computer controled. If the actual volume of delivered oil decreases under given limit (under setting point of flow indicator BQ4 → BQ4 is OFF ), is this evaluated as a fault and indicated on display of APT as ALARM:

**INFLOW TO LOW  
FOR CHECK & REPLACE  
INPUT FILTERS  
PUSH F4**

Now is computer asking which filter we want check or replace

**FILTER INSERTS  
REPLACEMENT -  
FOR INLET FILTERS - F1  
FOR OUTLET FILTERS - F2**

Because we have trouble with oil inflow the key F1 is used.

**INLET FILTERS  
CHECK & REPLACEMENT  
VACUATION  
WAIT**

Suction side of separator is provided with two filters - first stage drum (metal cloth) rough filter ( See Position 2 on Fig.4) and second stage fine (car) filter (See Position 3 on Fig 4). Both are situated on rear side of separator and have to be checked or replaced together.

To avoid the oil loss is the whole check & removal procedure made under proper vacuum in the separator.

Inlet filter removal procedure always begins with checks of drum (rough) filter.

End of vacuation procedure is indicated as

**UNSCREW CAP OF  
ROUGH FILTER AND  
CHECK HIS CHOKING**

After checking and cleaning of rough filter we get following display

**ROUGH FILTER OK ?**

**YES – ENTER**

if is rough filter closed with cap again we can confirm it by ENTER

and replacement procedure of fine filter (See Position 3 on Fig.4 ) is performed

**UNSCREW FINE FILTER  
SCREW ON NEW FILTER**

As fine filter normal car filter can be used See Table

Alternative Inlet Filters

FIAAM	FT 5044
FRAM	PH 4854
MANN & H	W 950/4
PUROLATOR	PER 316 - OC 105

And computer asks if the procedure is finished

**INLET FILTERS  
CHECKED & REPLACED ?**

**YES - ENTER**

and after pushing ENTER goes back to STARTUP Procedure

### 6.3 Replacement of filter inserts of ultrafilter

The degree of choking of filter inserts of ultrafilter is computer controlled.

If pressure loss of ultrafilter exceeds given level is this evaluated as Overpressure Alarm and after checking sequence described in Section 4.2 it is indicated as

**ULTRAFILTER CHOKED**

**FOR REPLACEMENT  
PUSH F4**

After pushing of F4 PCD asks again what filters we want check or replace

	<b>FILTER INSERTS</b>
	<b>REPLACEMENT -</b>
	<b>FOR INLET FILTERS - F1</b>
	<b>FOR OUTLET FILTERS - F2</b>

We confirm our decision by pushing F2

**OUTFLOW FILTERS  
CHECK & REPLACEMENT  
ULTRAFILTER  
VACUATED WAIT**

To avoid the oil loss the whole check & removal procedure have to be made under proper vacuum in the ultrafilter and separator.

Proper underpressure is indicated as

**VACUUM OK , UNTIGHT  
LIGHTLY ALL CENTRAL  
SCREWS - WAIT  
OIL EXHAUST IS ON**

Under this conditions (all central screws are slightly untight), atmospheric air slowly and uniformly forces oil from all chambers of ultrafilter back in vacuum in the separator. The end of this procedure is indicated as

**LIFT OFF ALL CAPS  
REPLACE FILTER INSERTS  
IF ALL REPLACED  
PUSH ENTER**

After pushing ENTER goes PCD back into STARTUP procedure.

## Chapter 7 . Electrical circuits

Power Circuit diagram is shown on Fig. 8

Name	Function	Designation	Qty.	Producer
------	----------	-------------	------	----------

### MAIN SWITCH BOX

QM1	Main switch	3LD2103-OTK53	1	Siemens
-----	-------------	---------------	---	---------

QF1	Heater breaker	5SX2 316-6	1	Siemens
QF2	Motor pump breaker	3RV11-1CA10	1	Siemens
QF3	Power supply unit breaker	5SX2 116-6	1	Siemens

KM1	Motor pump contractor-direct run	3RT1016-1BB42	1	Siemens
KM2	Heater contractor	3RT1016	1	Siemens
KM3	Motor pump contractor –reverse run	3RT1016	1	Siemens

FU1	Transformer	T2,5A, 5x20		GES Electronics
FU2	Cooling	T4,0A, 5x20		GES Electronics
FU3	Servovalve Belimo	T1,0A, 5x20		GES Electronics
FU4	Power supply 24DVC	T5,0A, 5x20		GES Electronics
FU5	Modem	T1,0A, 5x20		GES Electronics
FU6	Fan	T2,5A, 5x20		GES Electronics

### HERMETIZED GEAR PUMP

M1	Gear pump motor	1LA7080-4AA11	1	Siemens
GS1	Frequency changer	Micromaster 420	1	Siemens

### HEATER

EH1,1-1,3	Heating rod	14011/06 400V, 7500W	3	Eltop
ST1	Thermostat	TH160.2	1	Elfetex

### COOLING UNIT

M3	Compressor (standard version)	GD36AA, 230v	1	Electrolux
	or tropical climate over 40C	YB-645 GTD	1	Mitsubishi
YV1	Solenoid valve	HM2, 230V	1	Castel
ST0	Thermostat	F/2000	1	PRODIGY
M2	Fan motor	4656 N		Pabst

**AC/DC Supply**

TM1	Transformer	51265-P1S2	1	NT MAGNETICS
VD1	rectifier		1	Altmann
TM0	Autotransformer ( special order - only for insulated grids)	TAC 35052-0010	1	Elektrov Znojmo

**AIR CONDITIONER**

M4	Fan	7450 ES	1	Pabst
ST 01	Thermostat	F/2000	1	PRODIGY

**CONTROL & SUPPLY UNIT**

PCD	Proces Control Unit	ART 4000F	1	AMIT
KA1,3,4	Power switch – compressor, water batch, oil input Belimo	3TX7004-1MBO	3	Siemens
KA2	Power switch - defrost	3TX7004-3AC03	1	Siemens
KA5	Power switch – oil output Belimo	3TX7002-1FB02	1	Siemens

**COMMUNICATION UNIT**

	Modem		1	US Robotics
	or GSM Modem	TC35i Terminal	1	Siemens

**Process sensors 4-20 mA**

BP1	Pressure sensor	DMP331 0 – 6 b	1	BD Sensors
BP2,3,4	Pressure sensor	DMP331 0 – 2.5b	1	BD Sensors
BT1	Temperature sensor	Flexitemp 60 -50 +60°C	1	JSP Jicin
BT2,3	Temperature sensor	TG5 0 – 100°C		APO Elmos

**ON/OFF sensors**

BQ1	Batch unit (water level)	WLS1	1	Altmann
BQ2	Water trap (water level)	WLS1	1	Altmann
BQ3	Leakage sensor	RSF54Z100RC	1	Cynergy 3
FV1	Rotation direction/Voltage check & Reading relay	3Ug4615-1CR20	1	Siemens

**Lighting switch**

S1	Limit switch	HL408	1	GES Electronics
----	--------------	-------	---	-----------------






Fig. 8 Power circuit diagram




Fig 9 Control Circuit Diagram

## Chapter 8 - Remote Control

### 8.1 Program installation

Program OPTIM D3L - delivered CD disk - contains the main program for the remote (and in situ) control and the monitoring of VS-06 and additional sub-programs that enable an easy installation of the whole firmware into your computer.

Installation procedure:

- insert ALTMANN CD into disk drive (usually **D**)

under a normal operational condition is CD installed automatically


if not

- choose **START** and press **RUN**
- type **D:\setup.exe.** into the command line
- Press **OK (Enter)** to confirm the procedure.
- After the **SETUP** panel has appeared, click on **TARGET** and choose the target directory into which you want to install the program. The program will offer you one of the possibilities ( C:\ Altmann ). Press OK to accept this offer
- Click on **START** and program SETUP will install program ALTMANN into your computer
- Press **OK (Enter)** to confirm the procedure

**and your PC will offer you a window with the firm icon.**




### 8.2 Starting the program




Click on the Altmann's firm icon to launch the program.

Having launched the program basic windows will appear.




The toolbar contains the following buttons and tools -  
click on particular buttons of the toolbar to enter various applications



### 8.3. Remote communication

Click on the icon opens the new window for the choice of the telephone number of the desired separator.




**Attention :** Before beginning a communication the programming of **Communication Setup** and **Telephone directory** is necessary

After click on the **Connect** the modem is started and the connection realized. The operational data separator are transfered at three time levels and summoned under auxiliary toolbar:




## 8.4 Data Transfer Button

- last seven days ( button **Days**)



- last 24 hours (button **Hours**)



- last 240 min. (button **VirtualOn-Line**)

**OPTIM - On-Power Transformer Insulation Maintenance**

File Edit Action Options Help

9:32:42

Days Hours Virtual On-Line Parameters Dehydration and Degassing Log (DDL) Dielectric Strength Log (DSL)

Time	P1 [kPa]	P2 [kPa]	P3 [kPa]	T1 [C]	T2 [C]	T3 [C]
7:16:00	249.30	3.38	72.93	-4.28	51.79	35.34
7:17:00	244.89	3.07	72.93	-12.25	43.75	35.34
7:18:00	105.91	4.60	72.93	-4.28	53.26	35.34
7:19:00	250.77	4.91	72.93	-12.37	46.31	35.34
7:20:00	249.30	3.99	72.62	-5.02	47.04	35.34
7:21:00	249.30	3.38	72.93	-12.86	50.70	35.34
7:22:01	240.48	3.38	72.93	-5.75	43.38	35.34
7:23:01	105.17	5.83	72.93	-13.72	53.99	35.34
7:24:00	250.04	4.91	72.93	-7.10	46.31	35.34
7:25:00	250.04	3.99	72.62	-14.33	47.77	35.34
7:26:00	249.30	3.68	72.62	-7.96	50.33	35.34
7:27:00	107.38	4.91	72.93	-14.70	43.38	35.34
7:28:00	250.04	6.44	72.62	-8.33	53.99	35.34
7:29:00	249.30	4.30	72.62	4.91	45.58	35.34
7:30:00	250.04	3.99	72.62	13.00	48.50	35.34

Data loaded : 6.5.2011 9:15:16 EDF Arly

and the same toolbar contains a table **Parameters** which enables the remote re-programming of the vacuum separator (See Parametrical Programming)

**OPTIM - On-Power Transformer Insulation Maintenance**

File Edit Action Options Help

11:32:10

Days Hours Virtual On-Line Parameters

<b>Start-up</b>		<b>Dehydration</b>	
P1min	40 kPa	Tmax	20 min
P2min	40 kPa	T1min	-10 C
DP1	15 kPa	DT1	1 C
P2auto	120 kPa	T1max	12 C
<b>H-V Cycle</b>		Todt	3 min
P2max	250 kPa	T1alarm	25 C
DP2	4 kPa /s	<b>Oil heating</b>	
P2VC	15 kPa	T2max	50 C
P2ATM	105 kPa	DT2	5 C
DTVc	30 s	T2alarm	85 C
P2minvac	3 kPa	<b>Breakdown</b>	
P3auto	110 kPa	Podstav	85 kPa

Send to AMIT

Data loaded : 7.1.2005 12:33:06 staning



**8.5 . Return button** – enables return into a main window



**8.6 Archive**

Click on button **Archive** opens a data table which contains all **Days** data from the beginning a drying procedure at the given transformer. This database is automatically actualized by click on **Connect**. The database Archive contains data all maintained transformers by the given separator and is saved at a remote PC level .

Archiv							
Data							
Date	MWT [ml/day]	MWC [ml]	Ttb [C]	T1S [C]	P2S [kPa]	Qw[ppm]	
29.09.2015	0.00	0.00	0.00	0.00	0.00	0.00	
30.09.2015	0.00	0.00	0.00	0.00	0.00	0.00	
01.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
02.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
03.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
04.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
05.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
06.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
07.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
08.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
09.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
10.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
11.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
12.10.2015	0.00	0.00	0.00	0.00	0.00	0.00	
13.10.2015	0.00	7 964.00	56.81	-8.84	6.51	23.95	
14.10.2015	220.00	8 184.00	56.99	-9.10	6.87	24.07	
15.10.2015	44.00	8 228.00	56.44	-9.11	6.58	23.52	
16.10.2015	44.00	8 272.00	56.83	-8.99	6.61	23.78	
17.10.2015	88.00	8 360.00	57.21	-8.94	6.60	23.74	
18.10.2015	88.00	8 448.00	56.83	-9.00	6.69	23.67	
19.10.2015	44.00	8 492.00	56.90	-9.14	6.64	23.82	


Location history	
Start date	Location
19.4.2011	EDF Arly

Date - start: 24.11.2005  
Date - end: 19.10.2015

Close

and click on the graph button under the data column opens time-related data visualisation



For detailed data evaluation See Section 12 and 13.



**8.5 . Return button** – enables return from the Data Transfer into a main window




**8.6 Archive**

Click on button **Archive** opens a data table which contains all **Days** data from the beginning a drying procedure at the given transformer. This database is automatically actualized by click on **Connect**. The database Archive contains data all maintained transformers by the given separator and is saved at a remote PC level .

DATUM	MWT [ml/day]	MWC [ml]	TTS [C]	T1S [C]	P2S [kPa]	CW[ppm]
15.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
16.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
17.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
18.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
19.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
20.12.2004	0.00	50.00	29.86	-5.05	81.54	0.00
21.12.2004	25.00	75.00	36.35	-4.84	24.74	0.00
22.12.2004	25.00	100.00	39.02	-4.28	20.93	0.00
23.12.2004	50.00	150.00	42.35	-4.11	17.68	0.00
24.12.2004	25.00	175.00	40.81	-4.21	15.63	0.00
25.12.2004	25.00	200.00	39.13	-3.93	13.76	0.00
26.12.2004	50.00	250.00	42.44	-3.72	13.05	0.00
27.12.2004	25.00	275.00	39.10	-3.69	12.80	0.00
28.12.2004	50.00	325.00	41.79	-3.61	12.82	0.00
29.12.2004	25.00	350.00	38.79	-3.92	12.23	0.00
30.12.2004	25.00	375.00	38.87	-3.87	12.40	0.00
31.12.2004	25.00	400.00	39.06	-3.89	12.31	0.00
01.01.2005	25.00	425.00	39.33	-3.64	12.27	0.00
02.01.2005	25.00	450.00	37.73	-3.88	12.44	0.00
03.01.2005	25.00	475.00	41.18	-4.03	12.42	0.00
04.01.2005	25.00	500.00	43.04	-3.83	12.25	0.00

Date - start: 14.08.2003  
Date - end: 04.01.2005

and click on the graph button under the data column opens time-related data visualisation



For detailed data evaluation See Section 12 and 13.





## 8.8 Telephone directory

The „telephone directory“ database is used to avoid mistakes and for fast choice of the communication with the separator.

For actualizing choose button on the toolbar

Name	Connect	Directory
doma	74	doma
TRAFOSEAL EMEIII	0724054650	EMEIII

Click on **NEW** to define the connection with a newly installed separator - a new „card“ of the telephone directory will appear.

It is possible to write down in the **new record** very carefully all desired data concerning given transformer to avoid a very unpleasant mutual exchange of maintained transformers.

- (identification) name - **customer name, location, Serial Number** (S/N) of a given transformer
- connection
  - ❑ having chosen the **modem** connection write down into the **Phone** window:
    - ◆ the number of the telephone line assigned to the separator
    - ◆ or the number of the separator GSM modem
    - ◆ the COM connection is destined for a direct cable connection of PC or lap-top with an internal computer ( for detailed in-situ data transfer procedure See ....)
- Put down the name of the directory where you will archive the monitored data
- Click on **Save** to put down required connection in memory

Button **Edit** serves to actualize records in the telephone directory. Click on **Edit** to open the following window

**Edit item**

Name:

Connection: ☒ modem ☐ COM


Phone number:

Directory:

☒ Save ☒ Cancel

where you can change any items and confirm it by the button **Save** or you can the change cancel by click on button **Cancel**.

If you need to cancel any record from the **Telephone directory** you can do it very easy by click on **Delete** and the following window will be opened



and confirm clicking on **Ano** (Yes) or you can go back to **Telephone Directory** by click on **Ne** (No).

### 8.9 Save

click on Save will store data Days, Hours, Virtual-On line a Parameters of a given separator into a time- specified file.

### 8.10 Open

This command opens time-specified files and shows them under Optim A enviroment (See Data Transfer).

### 8.11 Copy to Clipboard


Command **Copy to Clipboard** saves the data from the actual screen into a clipboard file and this packet can be freely used e.g. by Excel.

### 8.12 Standard communication with the separator


After setup you can start proper communication between your PC and the separator pushing button



this action will open a panel




after you have finished the choice of a particular number, click on **Connect** – it will start the communication (RUNDMODEM procedure) and will show the following panel




if the connection fails, the program opens the following window

This may happen when the phone or GSM network is busy – simply repeat the process to get the connection.



After achieved the satisfactory connection the program loads the data from PCD in your PC and shows them in the main window.



In order to cut communication fees, the program always works off-line – takes the pre-worked data from PCD, checks them and switches off the connection.

The program offers implicitly so called Days data first – this means the PCD measured 6 quantities are averaged over 24 hours and stored in PCD for 7 days.

Together with the day values the program also loads so called Hours data – PCD measured 5 quantities are averaged over 1 hour and stored in PCD for 24 hours.

Day and hour averages can be also showed in the form of diagrams pushing the graph button below each column of the values.

The same is used for the Virtual On-Line procedure which dominantly serves as a check of the proper function of vacuum separator self.

The PCD of the separator can ( only on demand of PC ! ) implicitly scan , average and store the following basic values send at any time to the remote user PC:

MWT ....	water removal rate (ml/24 day)
MWC.....	total amount of water removed from a particular transformer (ml)
TTS ....	temperature of the transformer derived from oil temperature inflowing into the separator [°C]
T1S .....	temperature of freezing trap [°C]
P2S	averaged vacuum of separation process [kPa]
CWS	water content in inflowing oil [ppm] ( if humidity sensor is installed )

### 8.13 Parametric process control

To optimize of the separator function and the dehydration process of the transformer, click on button **Parameters** . This action will open the following panel

The screenshot shows the 'Parameters' panel of the OPTIM software. The panel is divided into several sections for parameter configuration:

- Start-up:** P1min (40 kPa), P2min (40 kPa), DP1 (15 kPa), P2auto (120 kPa).
- H-V Cycle:** P2max (250 kPa), DP2 (4 kPa /s), P2VC (15 kPa), P2ATM (105 kPa), DTVC (30 s), P2minvac (3 kPa), P3auto (110 kPa).
- Dehydration:** Tmax (20 min), T1min (-10 C), DT1 (1 C), T1max (12 C), Todt (3 min), T1alarm (25 C).
- Oil heating:** T2max (50 C), DT2 (5 C), T2alarm (85 C).
- Breakdown:** Podstav (85 kPa).

At the bottom right of the panel is a button labeled 'Send to AMIT'. The status bar at the bottom indicates 'Data loaded : 7.1.2005 12:33:06' and 'staning'.

Every basic function of the separator (from start up to shut down) can be parametrically programmed, but:

#### ATTENTION !!

Except for the temperature T2MAX (the required output temperature of the preheater) and P2auto (the required pressure of oil for automatic restart), no change of parameters is advisable. Parameters are already optimally pre-set.

If you want to change any parameter consult it with your dealer or producer of the separator first.

Adjusting parameters

- Re-write the given parameter to change it

- Click on button **Send to AMIT** to send the changed value back to the separator PCD

### 8.14 Transformer dehydration record

For the dehydration record and an evaluation of achieved results the procedure **Archive** is obviously used.

Click on




and this

step will be confirmed showing the panel


DATUM	MWT [ml/day]	MWC [ml]	TTS [C]	T1S [C]	P2S [kPa]	CW[ppm]
15.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
16.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
17.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
18.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
19.12.2004	0.00	0.00	0.00	0.00	0.00	0.00
20.12.2004	0.00	50.00	29.86	-5.05	81.54	0.00
21.12.2004	25.00	75.00	36.35	-4.84	24.74	0.00
22.12.2004	25.00	100.00	39.02	-4.28	20.93	0.00
23.12.2004	50.00	150.00	42.35	-4.11	17.68	0.00
24.12.2004	25.00	175.00	40.81	-4.21	15.63	0.00
25.12.2004	25.00	200.00	39.13	-3.93	13.76	0.00
26.12.2004	50.00	250.00	42.44	-3.72	13.05	0.00
27.12.2004	25.00	275.00	39.10	-3.69	12.80	0.00
28.12.2004	50.00	325.00	41.79	-3.61	12.82	0.00
29.12.2004	25.00	350.00	38.79	-3.92	12.23	0.00
30.12.2004	25.00	375.00	38.87	-3.87	12.40	0.00
31.12.2004	25.00	400.00	39.06	-3.89	12.31	0.00
01.01.2005	25.00	425.00	39.33	-3.64	12.27	0.00
02.01.2005	25.00	450.00	37.73	-3.88	12.44	0.00
03.01.2005	25.00	475.00	41.18	-4.03	12.42	0.00
04.01.2005	25.00	500.00	43.04	-3.83	12.25	0.00

Date - start: 14.08.2003  
Date - end: 04.01.2005

For a better understanding of a on-line drying process of a transformer is most often used time-related graphical output which is initialized by click on the graph button under chosen columns e.g. MWC (total amount of water removed from the given transformer)



and TTS (transformer temperature )



The comparison of both time-related graphs gives us very often plausible answer at a basic questions about the drying process.

In this case is quite obvious that the reduction of the amount of removed water was induced by the strong decline of the transformer temperature.

#### 8.15 Optimization of the on-power dehydration of transformers .

**The relevant moisture and dielectric diagnostics is always absolutely necessary before the beginning of any dehydration procedure.**

**The SIMMS and TRACONAL should be used to evaluate the water content in the cellulose materials of the transformer.**

**To avoid a overdrying of transformer the dehydration target has to be defined .**

Do not forget, regardless of how efficient any method of oil dehydration might be, the water removal from the transformer under normal operational conditions - the **transformer dehydration** - is ultimately governed by slow diffusion of moisture from cellulose and this process can be accelerated only by high temperature.

That is why you always have to describe any dehydration process of **transformer** with at least two values – **MWT** (average water removal rate and ) or **MWC** (total amount of removed water) and **TTS** ( temperature of the transformer).

**In order to avoid lowering the immediate reliability of the transformer we have to tune at least two antagonistic criteria:**

- max. separating efficiency of the separator (max. water removal rate)
- dielectric strength of oil - has to be maintained or improved

**The first criterion is fully understandable – we want to dehydrate the transformer as soon as possible. Thus we need to release maximum of water from the cellulose into the oil filling by raising the temperature of the transformer.**

**This fundamentally collides with the second criterion – if the temperature of the wet transformer will be too high, water contents in oil may easily exceed 30 ppm limit and the dielectric strength of oil drops relatively quickly under 40 – 50 kV/2.5mm.**

**If the moisture sensor is installed, follow always its on-line reading. The Cw-value should never exceed 30 ppm.**

To solve the dilemma between both criteria the method of gradual heating of the transformer is recommended especially if an on-line Cw-reading isn't available:

- check at first both actual values of water content in the oil (Cw-value) and dielectric strength of the oil (Ud-value).
  - If the Cw-value is substantially under 30 ppm, increase the temperature TTS of the transformer, about 10 °C, wait 5 days and check the result, if necessary, repeat the procedure until the Cw-value is about 20 – 25 ppm is reached
  - If the Cw-value is about 30 ppm, decrease the temp. ca 5 °C, check the result
  - If the Cw-value is substantially over 30 ppm, the temp. has to be immediately decreased until the allowed Cw-level is reached and simultaneously the Ud-level will be over 30 kV/2.5mm.

***To make the whole procedure easier, the on-line reading of the Cw-value is recommended – the installation of a proper moisture sensor in the separator is very simple.***

- check daily water removal rate MWT and the transformer temperature TTS on your PC
- when MWT is between 50 – 120 ml/day (and TTS is virtually constant) and the dehydration process is OK operate the transformer at this temperature until the output decreases below 50 ml per day (or any lower output the operator chooses )
- when MWT drops to less than 50 ml/day, increase the transformer temperature TTS about 5 – 7°C .
- when MWT exceeds 120 ml/day decrease the temperature TTS about 2-5°C
- Repeat the preceding steps as many times as necessary to reach the maximum operating temperature of the transformer. (usually 65- 85°C)

## Chapter 9 The advanced evaluation of the effectivity of transformer treatment

For a better understanding of the long-term trends of dehydration effectivity of the VS-06 and a change of the dielectric behaviour of the transformer within the treatment two new procedures are used:

- the **DDL (Dehydration and Degassing Log)**
- the **DSL ( Dielectric Strength Log)**


Both procedures can be started by clicking on the DDL or the DSL buttons in the Main window. By clicking on the DDL it shows :

all the necessary basic data concerning :

- requested time-range of data (Data File , Start , End)
- Transformer Location, Transformer S/N and VS-06 S/N
- Maximal allowed water content in oil (Qw,max)


can be directly and easily entered from the keyboard.

By clicking on the Analyse button the time-related change of basic variables (Mwc, Ttb, P2S, Qw) are shown on the screen





and by clicking on the printer icon (in the upper part of the diagram), the diagram is converted into the user-friendly version. The end of the conversion is indicated as




and by clicking on the OK button, the final, printable output of the DDL procedure is shown

	<b>VACUUM SEPARATOR VS-06 - Main Data Log</b>
	<b>OPTIM D3L (Dehydration Degassing Dielectric Log)</b>
	<b>Procedure: DDL (Dehydration Degassing Log)</b>
	© Ing. Altmann, 2010

Transformer Location:	xxx
Transformer Serial Number:	xxx
VS-06 Serial Number:	xxxx

Time-period of evaluation : 19.04.2011 - 05.05.2011

Norm requested value  $Q_{w,max}$  - red horizontal line  
 $Q_{w,max} = 30$  ppm... maximum allowed water content in oil



Mwc	Amount of removed water (ml)
Qw	Water Content in oil (ppm)
Ttb	Transformer temperature bottom (C)
P2s	Averaged vacuum in Separator (kPa)

#### ATTENTION.

Water content in oil  $Q_w$  exceeded  
 allowed  $Q_{w,max}$ -limit:

Day	$Q_w$ (ppm)

#### Remarks & Recommendations

Date of evaluation: 6.5.2011

where all directly measured values are clearly defined and shown in the form of a time-related diagram.

A new kind of assesment can be used now for the on-line diagnostic of dielectric behaviour of the transformer

## DSL – Dielectric Strength Log

This absolutely new approach enables the DSL online to calculate the theoretical (maximum attainable) value of the dielectric strength of oil (the  $U_{d,t}$ -value) on the basis of the direct measuring of the water content in the oil (the  $Q_w$ -value).

This is the first time, that this specific online diagnosis can be validated by the offline data.

This mathematical model used for the calculation is based on the well documented near-linear relation between the decrease of dielectric strenght due to the increase of the relative humidity of oil (at lab temperature).

And this theoretical relationship can be verified by lab data.

By clicking on the DSL button the first Windows shows


And the following steps are similar as before :

- requested time-range of data (Data File , Start , End)
- Transformer Location, Transformer S/N and VS-06 S/N
- Minimum allowable dielectric strength of the oil ( Ud,min)


these can be directly and easily entered from the keyboard.

The DSL procedure enables a substantially more detailed insight into dielectric behaviour of a given transformer especially the „contardictory“ change of the dielectric strength versus the temperature of the transformer.

After clicking on the Analyse button the resulting time-related Ud,t-relation is shown on the screen together with bottom temperature of the transformer.



clicking on the printer icon shows




And clicking on the OK shows the description of the dielectric behaviour of the transformer for the requested time period

	<b>VACUUM SEPARATOR VS-06 - Main Data Log</b>
	<b>OPTIM D3L (Dehydration Degassing Dielectric Log)</b>
	<b>Procedure: DSL (Dielectric Strength Log)</b>
	© Ing. Altmann, 2010

Transformer Location:	xxx
Transformer Serial Number:	xxxx
VS-06 Serial Number:	xxxx

Time-period of evaluation : 19.04.2011 - 05.05.2011

Norm requested value  $U_{d,min}$  - blue horizontal line  
 $U_{d,min} = 30 \text{ kV/2.5mm}$ ... minimal allowed dielectric strength in oil



$U_{d,t}$  ... Theoretical Dielectric Strength of oil (kV/2.5mm)  
 $T_{tb}$  ... Transformer temperature bottom ( $^{\circ}\text{C}$ )

**ATTENTION.**  
 Dielectric Strength of oil  $U_{d,t}$  decreased  
 under allowed  $U_{d,min}$ -limit:

Number of lab verifications: 0

Day	$U_{d,t}(\text{kV/2.5mm})$

#### Remarks & Recommendations

Date of evaluation: 6.5.2011

To obtain relevant diagnostic results, the accuracy of the  $U_{d,t}$ -simulation for the given time-period must always be correspondingly verified:


- by the quantitative comparison of the  $U_{d,t}$ -value and the  $U_{d,lab}$ -value at the same time.

This means that the simulated  $U_{d,t}$ -value has to be compared with the  $U_{d,lab}$ -value at the same sampling time (the time when the oil for the lab  $U_d$ -reading has been sampled at the transformer).

The final result of the DSL-procedure is the quantitative verification by means of the Verification Table and the Verification Diagram.

By clicking on the Verification button in the DSL window, the Verification Table and the Verification Diagram is shown.

At first the time(s) of sampling and the corresponding  $U_{d,lab}$  value(s) and other lab values have to be entered into the Verification Table:



For example: the sampling of oil was performed 19.4 2011 at 16.00.

By clicking on the pre-defined date, here 19.4 2011, the day is marked (by the blue colouring of the row). To enter the lab data the [Edit row](#) button is used.

Verification

Date (day): 20.4.2011

Time (hour): 10:00

$U_{d,lab}$  (kV/2.5mm): 65


S (kV/2.5mm): 5

V (%): 6

$T_{lab}$  (C): 20

OK Cancel

Clicking on the OK button then gives the requested result(s), which is shown in the Verification Diagram in the bottom part of the window .



The Verification Diagram gives a direct and easy insight into the accuracy of on-line Ud,t-simulation and/or the Ud,lab-value :

- if the  $U_{d,lab} \approx U_{d,t}$ -point is situated in the 10kV/2.5mm band around the transverse  $45^\circ$  line, the consistency of the simulated Ud,t-value and the Ud,lab-value is very good and the subsequent diagnosis of the dielectric behaviour of the transformer for the given time-period is precise enough
- if the  $U_{d,lab} \approx U_{d,t}$ -point is situated in the 20kV/2.5mm band, the consistency of simulated Ud-value and measured Ud-value is sufficient (for field conditions) and the subsequent diagnosis is acceptable
- if the  $U_{d,lab} \approx U_{d,t}$ -point is situated outside of the 30kV/2.5 band, means that either the simulated Ud,t-value or the Ud,lab-reading is not precise enough. The relevant check of a dielectric behaviour of the transformer is not possible. Therefore the veracity of both values has to be checked.

The mutual comparison of simulated and directly measured Ud-values gives us an opportunity to check the plausibility of both values.